


GM-243C(TL) GM-243S(TL)


Audio Linked Telescopic Gooseneck Conference System

Gooseneck Conference System




IN-OUT Connection for Easy Set-Up

- Standard CAT.5e/CAT.6 cable for audio and power link.
- Lockable RJ45 jack prevents any loose cable and unauthorized meddling.



High System Capability or Audio Converter

Up to 120 microphones with two GMC-60 audio converters, ideal for medium / small company, office, corporate and school conference rooms.




Telescopic gooseneck for Various Usage

Telescopic, length-adjustable gooseneck avoids moving the base.



Intelligent Power Design

- Each GM-243 unit and switching power can be located anywhere in the loop with GMC-10+ audio converter.
- Only one switching power and audio converter needed for the entire system.



Chairman Priority Management

- Two chairman units available in a system.
- Priority button for chairman's temporary or permanent muting of delegate microphones.

5 min OFF

Automatically Mute after 5 Minutes Without Audio Input

- Easily identifiable indicator LED both on the gooseneck and the button.
- Automatically shutdown after idling for 5 minutes. (except GM-243C in priority mode)



** Specifications and design are subject to change without prior notice.

SPECIFICATIONS

Model	GM-243C(TL)	GM-243S(TL)
Cartridge	Uni-directional condenser	Uni-directional condenser
Impedance	680Ω	680Ω
Sensitivity	-50dB±3dB	-50dB±3dB
Distortion	< 0.5%	< 0.5%
S/N ratio	≥ 60dB	≥ 60dB
Frequency response	80Hz-16KHz	80Hz-16KHz
Max input SP	100dB for 1% T.H.D.	100dB for 1% T.H.D.
Display	LED	LED
Sound control	Yes	Yes
Chairman priority (MUTE)	Yes	No
Speech (TALK)	Yes	Yes
Gain control (GAIN)	Yes	Yes
Input/output jack	2	2
Working voltage	15V, 4.3A	15V, 4.3A
Dimension (HxWxD, mm)	479 x 110 x 162	479 x 110 x 162
Weight (g)	747	734

*** Specifications and design are subject to change without prior notice.*